

LIDDING FILMS



TECHNICAL SUPPORT

We pride ourselves in providing high quality services and technical support to all customers.

CONTACT INFORMATION

For more information on any of our products or services, please contact us at:

Golden Eagle Extrusions, Inc.
1762 State Route 131
Milford, Ohio 45150
P - 800.634.3355
F - 513.248.8300

www.goldeneagleextrusions.com
info@goldeneagleextrusions.com

LFO-120PP

STANDARD THICKNESS - 2.0 MIL

LFO-120PP is an Oriented Polypropylene laminated to a Cast Polypropylene. This material is designed for use with Polypropylene trays or trays with a Polypropylene seal layer. This film can be sealed at optimal adhesion at 320°, with a dwell time of 3 seconds.

Key Features

- Great for fresh-cut tomatoes and onions
- Suitable for “see through” packaging structure
- One side sealable
- Lock seal to PP trays

PROPERTIES	UNIT	TESTING METHOD	TYPICAL VALUES
MECHANICAL			
Tensile Strength			
MD	lb/in ²	ASTM D882	12,000
TD			11,600
Elongation			
MD	%	ASTM D882	90
TD			100
PHYSICAL			
Yield	in ² /lb		15,000
COF Sealant side		ASTM D1894	0.27
Heat resistant side			0.2
Haze	%	ASTM D 1003	3
BARRIER			
MVTR	g/100 in ² /day	ASTM F1249 38°C, 100%RH	0.25
OTR	cc/100 in ² /day	ASTM D3985 23°C, 0%RH	120
THERMAL			
Shrinkage			
MD	%	ASTM D1204	7
TD			4

Disclaimer: Nothing in this data sheet is to be taken as a warranty. Offered for your consideration only, the information provided herein represents our best knowledge and judgment. Golden Eagle Extrusions, Inc. assumes no liability whatsoever in connection with the use of this information.