

LIDDING FILMS



TECHNICAL SUPPORT

We pride ourselves in providing high quality services and technical support to all customers.

CONTACT INFORMATION

For more information on any of our products or services, please contact us at:

Golden Eagle Extrusions, Inc.
1762 State Route 131
Milford, Ohio 45150
P - 800.634.3355
F - 513.248.8300

www.goldeneagleextrusions.com
info@goldeneagleextrusions.com

LFO-270ANP

STANDARD THICKNESS - 2.7 MIL

DESCRIPTION:

Golden Eagle's LFO-320ANP is a 3-layer lamination, used primarily as a lidding film. This high barrier structure consists of AlOx, BON and a peelable CPP.

CHARACTERISTICS:

- Tremendous clarity
- Excellent Oxygen and Moisture barrier
- Peelable from PP trays

FDA STATUS:

Manufactured with materials compliant with FDA regulations.

PROPERTIES	UNIT OF MEASURE		
Thickness	Mil	3.2	
Yield	in ² /lb	9,900	
COF (Film to Film)	Kinetic	0.55	ASTM D1894
Haze (Wide Angle)	%	4.0	ASTM D1003
WVTR	g/100 in ² /24 hrs	<0.1	ASTM F1249
OTR	cc/100 in ² /24 hrs	<0.1	ASTM F1927

Disclaimer: Nothing in this data sheet is to be taken as a warranty. Offered for your consideration only, the information provided herein represents our best knowledge and judgment. Golden Eagle Extrusions, Inc. assumes no liability whatsoever in connection with the use of this information.