

LIDDING FILMS



TECHNICAL SUPPORT

We pride ourselves in providing high quality services and technical support to all customers.

CONTACT INFORMATION

For more information on any of our products or services, please contact us at:

Golden Eagle Extrusions, Inc.
1762 State Route 131
Milford, Ohio 45150
P - 800.634.3355
F - 513.248.8300

www.goldeneagleextrusions.com
info@goldeneagleextrusions.com

LFO-120BXP

STANDARD THICKNESS - 2.0 MIL

LFO-120BXP is a BOPP laminated to a peelable coextruded PP. This material is designed for use as a peelable lidding structure for Polypropylene trays or trays with a Polypropylene seal layer.

Key Features

- Great for fresh-cut tomatoes and onions
- Suitable for “see through” packaging structures
- One side sealable

PROPERTIES	UNIT	TESTING METHOD	TYPICAL VALUES
MECHANICAL			
Tensile Strength MD TD	lb/in ²	ASTM D882	12,000 11,600
Elongation MD TD	%	ASTM D882	90 100
PHYSICAL			
Yield	in ² /lb		15,000
COF Sealant side Heat resistant side		ASTM D1894	0.27 >.40
Haze	%	ASTM D 1003	43
BARRIER			
MVTR	g/100 in ² /day	ASTM F1249 38°C, 100%RH	0.25
OTR	cc/100 in ² /day	ASTM D3985 23°C, 0%RH	120
THERMAL			
Shrinkage MD TD	%	ASTM D1204	7 4

Disclaimer: Nothing in this data sheet is to be taken as a warranty. Offered for your consideration only, the information provided herein represents our best knowledge and judgment. Golden Eagle Extrusions, Inc. assumes no liability whatsoever in connection with the use of this information.